

## LOW PROFILE & U-SHAPE SCISSORS

Descriptio MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Max Length enlargment (mm)	U-space width (mm)	Max Width enlargemen (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JXL-5/80-	500	1350 x 600	1283 x 532	2000		800	800	80	19	0.48	180
JXL-5/80-	500	1350 x 800	1283 x 732	2000		1050	800	80	19	0.48	190
JXL-5/80-	500	1350 x 1050	1283 x 982	2000		1400	800	80	19	0.48	210
JXL-10/80	1000	1350 x 600	1283x532	2000		800	800	80	19	0.72	185
<b>JXL-10/80</b>	1000	1350 x 800	1283x732	2000		1050	800	80	19	0.72	200
<b>JXL-10/80</b>	1000	1350 x 1050	1283x982	2000		1400	800	80	19	0.72	220
JXL-20/80	2000	1400 x 800	1300x730	2100		1050	800	95	30	0.72	270
JXL-20/80	2000	1400 x 1200	1300x1180	2100		1500	800	95	30	0.72	300
<b>Ramp for closed height 80 mm</b>											
<b>Ramp for closed height 95 mm</b>											
JXU-5/80-	500	1350 x 1050	1283x982		600	-	800	80	19	0.48	185
<b>JXU-10/80</b>	1000	1350 x 1050	1283x982		600	-	800	80	19	0.72	200
JXU-20/80	2000	1400 x 1200	1300x1180		600	-	800	95	30	0.72	300
JXU-16/80	1600	1530 x 1670					800	85	15	1.4	580
JXU-16/80	1600	1530 x 1870					800	85	15	1.4	590

Note ! Remote power pack on all low profile lifts

## LOW PROFILE & U-SHAPE SCISSORS IN STAINLESS STEEL

Descriptio MODEL	Capacity (Kg)	Platform (L x W) (mm)	Base frame (L x W) (mm)	Max Length enlargment (mm)	U-space width (mm)	Max Width enlargemen (mm)	Lift stroke (mm)	Closed height (mm)	Lift time (sec)	Motor (kW)	Weight (kg)
JXL-8/80-	800	1350 x 800	1283 x 732				800	80	19	0.72	200
JXL-8/80-	800	1350 x 1050	1283 x 982				800	80	19	0.72	220
JXU-8/80-	800	1350 x 1050	1283 x 982				800	80	19	0.72	200

Note ! Remote power pack on all low profile lifts

## LOW PROFILE TANDEM SCISSOR TABLES

Descriptio MODEL	Capacity	Platform (L x W)	Base frame (L x W)	Max Length enlargment	Max Width enlargemen	Lift stroke	Closed height	Lift time	Motor	Weight
JXXL-0120	1200	2700x850		4000	1100	800	90	17	1.4	450
JXXL-0150	1500	2700x850		3400	1100	800	90	17	1.4	450
JXXL-0300	3000	2800x1100		4200	1400	800	130	28	1.4	650